

# AIR SHUT-OFF CLUTCH SCREWDRIVER



## AT-4110

Straight type lever to start shut-off air screwdriver  
(800 rpm)

## AT-4111

Straight type lever to start shut-off air screwdriver  
(1450 rpm)



## AT-4112

Pistol type shut-off air screwdriver  
(800 rpm)

## AT-4113

Pistol type shut-off air screwdriver  
(1450 rpm)



## AT-4114

Angle type shut-off air screwdriver  
(800 rpm)

## AT-4115

Angle type shut-off air screwdriver  
(1450 rpm)



## AT-4010

Push to start shut-off air screwdriver  
(750 rpm)

## AT-4011

Push to start shut-off air screwdriver  
(2500 rpm)



## AT-4010H

Push to start shut-off air screwdriver  
(750 rpm)

## AT-4011H

Push to start shut-off air screwdriver  
(2500 rpm)



## AT-4013

Push to start shut-off air screwdriver  
(1000 rpm)



## AT-4014

Push to start shut-off air screwdriver  
(950 rpm)

## AT-4015

Push to start shut-off air screwdriver  
(650 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Packing Pcs/Ctn/G.W/Cuft (kg)	Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>		
AT-4010	5/32	4	2	2500	1.8-3.1	0.2~0.35	7.00	178	1/4"	1/4"	4.0	113	0.77	0.35	90	6.3	10/Ctn/7Kg/0.9'	1.5
AT-4010H	1/4	6.35	2	2500	1.8-3.1	0.2~0.35	7.28	185	1/4"	1/4"	4.0	113	0.55	0.25	90	6.3	20/Ctn/8Kg/0.9'	1.5
AT-4011	5/32	4	2.5	750	3.1~8.9	0.35~1.0	7.48	190	1/4"	1/4"	4.0	113	0.82	0.37	90	6.3	10/Ctn/7Kg/0.9'	1.5
AT-4011H	1/4	6.35	2.5	750	3.1~8.9	0.35~1.0	7.60	192	1/4"	1/4"	4.0	113	0.60	0.27	90	6.3	20/Ctn/8.5Kg/0.9'	1.5
AT-4013	1/4	6.35	3.5	1000	10.6~19.5	1.2~2.2	9.02	229	1/4"	1/4"	5.0	142	1.56	0.71	90	6.3	20/Ctn/14Kg/1.4'	2
AT-4014	1/4	6.35	4~5	950	17.7~42.5	2.0~4.8	9.84	250	1/4"	1/4"	5.5	156	2.05	0.93	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4015	1/4	6.35	5~6	650	26.6~62	3.0~7.0	9.84	250	1/4"	1/4"	5.5	156	2.05	0.93	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4110	1/4	6.35	4	800	14.2~27.5	1.6~3.1	11.22	285	1/4"	1/4"	7.0	198	2.09	0.95	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4111	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	11.22	285	1/4"	1/4"	7.0	198	2.09	0.95	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4112	1/4	6.35	4	800	14.2~27.5	1.6~3.1	7.68	195	1/4"	1/4"	7.0	198	2.16	0.98	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4113	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	7.68	195	1/4"	1/4"	7.0	198	2.16	0.98	90	6.3	10/Ctn/12Kg/1.2'	2
AT-4114	1/4	6.35	5	800	19.5~38.1	2.2~4.3	13.39	340	1/4"	1/4"	7.0	198	2.69	1.22	90	6.3	10/Ctn/14Kg/1.2'	2
AT-4115	1/4	6.35	4	1450	10.6~21.3	1.2~2.4	13.39	340	1/4"	1/4"	7.0	198	2.69	1.22	90	6.3	10/Ctn/14Kg/1.2'	2

● Recommended Air Pressure : 90 psi (6.3 kg/cm<sup>2</sup>)

# AIR SHUT-OFF CLUTCH SCREWDRIVER PISTOL TYPE



## AT-4016P15

Shut-off clutch air screwdriver (1,500 rpm)

## AT-4016P11

Shut-off clutch air screwdriver (1,100 rpm)



## AT-4017P16

Shut-off clutch air screwdriver (1,600 rpm)

## AT-4017P09

Shut-off clutch air screwdriver (900 rpm)



## AT-4018P17

Shut-off clutch air screwdriver (1,700 rpm)

## AT-4018P11

Shut-off clutch air screwdriver (1,100 rpm)

## AT-4018P07

Shut-off clutch air screwdriver (700 rpm)



## AT-4019P17

Shut-off clutch air screwdriver (1,700 rpm)

## AT-4019P11

Shut-off clutch air screwdriver (1,100 rpm)

## AT-4019P07

Shut-off clutch air screwdriver (700 rpm)

## AT-4019P05

Shut-off clutch air screwdriver (550 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>	
AT-4016P15	1/4	6.35	M2	1500	2.7~7	0.3~0.8	8.4	214	1/4"	1/4"	5	142	1.54	0.7	70	5.0	2
AT-4016P11	1/4	6.35	M2	1100	3.5~8.8	0.4~1	8.4	214	1/4"	1/4"	5	142	1.54	0.7	70	5.0	2
AT-4017P16	1/4	6.35	M2~M3	1600	6.2~12	0.7~1.4	8.2	209	1/4"	1/4"	7	198	1.76	0.8	70	5.0	2
AT-4017P09	1/4	6.35	M3	900	9.7~18	1.1~2.1	8.2	209	1/4"	1/4"	7	198	1.76	0.8	70	5.0	2
AT-4018P17	1/4	6.35	M3	1700	8.8~25	1~2.8	9	228	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4018P11	1/4	6.35	M3~M4	1100	8.8~30	1~3.4	9	228	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4018P07	1/4	6.35	M3~M4	700	8.8~40	1~4.5	9	228	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4019P17	1/4	6.35	M4	1700	17.6~38	2~4.3	9	228	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019P11	1/4	6.35	M4~M5	1100	22~52	2.5~5.9	9	228	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019P07	1/4	6.35	M5	700	26.4~70	3~8	9	228	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019P05	1/4	6.35	M6	550	26.4~96	3~10.9	9	228	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2

# AIR SHUT-OFF CLUTCH SCREWDRIVER STRAIGHT TYPE / PUSH START

**AT-4016S15**  
Shut-off clutch air screwdriver (1,500 rpm)  
**AT-4016S11**  
Shut-off clutch air screwdriver (1,100 rpm)



**AT-4017S16**  
Shut-off clutch air screwdriver (1,600 rpm)  
**AT-4017S09**  
Shut-off clutch air screwdriver (900 rpm)



**AT-4018S17**  
Shut-off clutch air screwdriver (1,700 rpm)  
**AT-4018S11**  
Shut-off clutch air screwdriver (1,100 rpm)  
**AT-4018S07**  
Shut-off clutch air screwdriver (700 rpm)



**AT-4019S17**  
Shut-off clutch air screwdriver (1,700 rpm)  
**AT-4019S11**  
Shut-off clutch air screwdriver (1,100 rpm)  
**AT-4019S07**  
Shut-off clutch air screwdriver (700 rpm)  
**AT-4019S05**  
Shut-off clutch air screwdriver (550 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>	
<b>AT-4016S15</b>	1/4	6.35	M2	1500	2.7~7	0.3~0.8	8.5	216	1/8"	1/4"	5	142	0.66	0.3	70	5.0	2
<b>AT-4016S11</b>	1/4	6.35	M2	1100	3.5~8.8	0.4~1	8.5	216	1/8"	1/4"	5	142	0.66	0.3	70	5.0	2
<b>AT-4017S16</b>	1/4	6.35	M2~M3	1600	6.2~12	0.7~1.4	9	229	1/8"	1/4"	7	198	1.32	0.6	70	5.0	2
<b>AT-4017S09</b>	1/4	6.35	M3	900	9.7~18	1.1~2.1	9	229	1/8"	1/4"	7	198	1.32	0.6	70	5.0	2
<b>AT-4018S17</b>	1/4	6.35	M3	1700	8.8~25	1~2.8	10	254	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
<b>AT-4018S11</b>	1/4	6.35	M3~M4	1100	8.8~30	1~3.4	10	254	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
<b>AT-4018S07</b>	1/4	6.35	M3~M4	700	8.8~40	1~4.5	10	254	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
<b>AT-4019S17</b>	1/4	6.35	M4	1700	17.6~38	2~4.3	10.1	256	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
<b>AT-4019S11</b>	1/4	6.35	M4~M5	1100	22~52	2.5~5.9	10.1	256	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
<b>AT-4019S07</b>	1/4	6.35	M5	700	26.4~70	3~8	10.1	256	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
<b>AT-4019S05</b>	1/4	6.35	M6	550	26.4~96	3~10.9	10.1	256	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2

# AIR SHUT-OFF CLUTCH SCREWDRIVER STRAIGHT TYPE / LEVER START



## AT-4016L15

Shut-off clutch air screwdriver (1,500 rpm)

## AT-4016L11

Shut-off clutch air screwdriver (1,100 rpm)



## AT-4017L16

Shut-off clutch air screwdriver (1,600 rpm)

## AT-4017L09

Shut-off clutch air screwdriver (900 rpm)



## AT-4018L17

Shut-off clutch air screwdriver (1,700 rpm)

## AT-4018L11

Shut-off clutch air screwdriver (1,100 rpm)

## AT-4018L07

Shut-off clutch air screwdriver (700 rpm)



## AT-4019L17

Shut-off clutch air screwdriver (1,700 rpm)

## AT-4019L11

Shut-off clutch air screwdriver (1,100 rpm)

## AT-4019L07

Shut-off clutch air screwdriver (700 rpm)

## AT-4019L05

Shut-off clutch air screwdriver (550 rpm)



Model No.	Hex. Shank Size		Capacity Bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>	
AT-4016L15	1/4	6.35	M2	1500	2.7~7	0.3~0.8	9.29	236	1/8"	1/4"	5	142	0.66	0.3	70	5.0	2
AT-4016L11	1/4	6.35	M2	1100	3.5~8.8	0.4~1	9.29	236	1/8"	1/4"	5	142	0.66	0.3	70	5.0	2
AT-4017L16	1/4	6.35	M2~M3	1600	6.2~12	0.7~1.4	9.61	244	1/8"	1/4"	7	198	1.32	0.6	70	5.0	2
AT-4017L09	1/4	6.35	M3	900	9.7~18	1.1~2.1	9.61	244	1/8"	1/4"	7	198	1.32	0.6	70	5.0	2
AT-4018L17	1/4	6.35	M3	1700	8.8~25	1~2.8	10.79	274	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4018L11	1/4	6.35	M3~M4	1100	8.8~30	1~3.4	10.79	274	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4018L07	1/4	6.35	M3~M4	700	8.8~40	1~4.5	10.79	274	1/4"	1/4"	8	226	1.76	0.8	85	6.0	2
AT-4019L17	1/4	6.35	M4	1700	17.6~38	2~4.3	10.67	271	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019L11	1/4	6.35	M4~M5	1100	22~52	2.5~5.9	10.67	271	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019L07	1/4	6.35	M5	700	26.4~70	3~8	10.67	271	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2
AT-4019L05	1/4	6.35	M6	550	26.4~96	3~10.9	10.67	271	1/4"	1/4"	9	255	1.76	0.8	85	6.0	2

# AIR SHUT-OFF CLUTCH SCREWDRIVER ANGLE TYPE



## AT-4016A15

Shut-off clutch air screwdriver (1,500 rpm)

## AT-4016A11

Shut-off clutch air screwdriver (1,100 rpm)



## AT-4017A16

Shut-off clutch air screwdriver (1,600 rpm)

## AT-4017A09

Shut-off clutch air screwdriver (900 rpm)



## AT-4018A17

Shut-off clutch air screwdriver (1,700 rpm)

## AT-4018A11

Shut-off clutch air screwdriver (1,100 rpm)

## AT-4018A07

Shut-off clutch air screwdriver (700 rpm)



## AT-4019A11

Shut-off clutch air screwdriver (1,100 rpm)

## AT-4019A07

Shut-off clutch air screwdriver (700 rpm)

## AT-4019A05

Shut-off clutch air screwdriver (550 rpm)



Model No.	Hex. Shank Size		Capacity bolt Size	Free Speed RPM	Max. Torque		Overall Length		Air Inlet (PT)	Air Hose (ID)	Avg. Air Consumption		Net Weight		Working Air Pressure		Sug. Air Comp. (HP)
	inch	mm			in-lb	N-m	inch	mm			scfm	l/min	lb	kg	psi	kg/cm <sup>2</sup>	
AT-4016A15	1/4	6.35	M2	1500	2.7~7	0.3~0.8	11.18	284	1/8"	1/4"	5	142	0.88	0.4	70	5.0	2
AT-4016A11	1/4	6.35	M2	1100	3.5~8.8	0.4~1	11.18	284	1/8"	1/4"	5	142	0.88	0.4	70	5.0	2
AT-4017A16	1/4	6.35	M2~M3	1600	6.2~12	0.7~1.4	11.46	291	1/8"	1/4"	7	198	1.76	0.8	70	5.0	2
AT-4017A09	1/4	6.35	M3	900	9.7~18	1.1~2.1	11.46	291	1/8"	1/4"	7	198	1.76	0.8	70	5.0	2
AT-4018A17	1/4	6.35	M3	1700	8.8~25	1~2.8	12.64	321	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4018A11	1/4	6.35	M3~M4	1100	8.8~30	1~3.4	12.64	321	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4018A07	1/4	6.35	M3~M4	700	8.8~40	1~4.5	12.64	321	1/4"	1/4"	8	226	2.42	1.1	85	6.0	2
AT-4019A11	1/4	6.35	M4~M5	1100	22~52	2.5~5.9	12.68	322	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019A07	1/4	6.35	M5	700	26.4~70	3~8	12.68	322	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2
AT-4019A05	1/4	6.35	M6	550	26.4~96	3~10.9	12.68	322	1/4"	1/4"	9	255	2.42	1.1	85	6.0	2